

**This Page Is Inserted by IFW Operations  
and is not a part of the Official Record**

## **BEST AVAILABLE IMAGES**

**Defective images within this document are accurate representations of the original documents submitted by the applicant.**

**Defects in the images may include (but are not limited to):**

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**
- **BLANK PAGES**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**

Express Mail #EK83042771845  
DE920000002US1



Eur päisches  
Patentamt

European  
Patent Office

Office eur péen  
des brevets

J1036 U.S. PTO  
09/872878  
06/01/01

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

00111784.5

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

I.L.C. HATTEN-HECKMAN

DEN HAAG, DEN  
THE HAGUE, 12/12/00  
LA HAYE, LE

**THIS PAGE BLANK (USPTO)**



**Eur päisches  
Patentamt**

**European  
Patent Office**

**Office européen  
des brevets**

**Blatt 2 der Bescheinigung  
Sheet 2 of the certificate  
Page 2 de l'attestation**

Anmeldung Nr.:  
Application no.: 00111784.5  
Demande n°:

Anmeldetag:  
Date of filing: 03/06/00  
Date de dépôt:

Anmelder:  
Applicant(s):  
Demandeur(s):  
**International Business Machines Corporation**  
**Armonk, NY 10504**  
**UNITED STATES OF AMERICA**

Bezeichnung der Erfindung:  
Title of the invention:  
Titre de l'invention:  
**Archiving in workflow-management-systems**

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:  
State:  
Pays:

Tag:  
Date:  
Date:

Aktenzeichen:  
File no.  
Numéro de dépôt:

Internationale Patentklassifikation:  
International Patent classification:  
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:  
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR  
Etats contractants désignés lors du dépôt:

Bemerkungen:  
Remarks:  
Remarques:

**THIS PAGE BLANK (USPTO)**

## DESCRIPTION

EPO - Munich  
38  
03. Juni 2000

## Archiving in Workflow-Management-Systems

Background of the InventionField of the Invention

The present invention relates to Workflow-Management-Systems. More particularly the present invention relates to a method of optimizing Workflow-Management-Systems.

Description and Disadvantages of Prior Art

A new area of technology with increasing importance is the domain of Workflow-Management-Systems (WFMS). WFMS support the modeling and execution of business processes. Business processes executed within a WFMS environment control which piece of work of a network of pieces of work will be performed by whom and which resources are exploited for this work. The individual pieces of work might be distributed across a multitude of different computer systems connected by some type of network. A thorough representation of WFMS technology is given by Frank Leymann, Dieter Roller, Production Workflow: Concepts and Techniques, Prentice-Hall, Upper Saddle River, New Jersey, 1999.

The product "IBM MQSeries Workflow" represents such a typical modern, sophisticated, and powerful workflow management system. It supports the modeling of business processes as a network of activities. This network of activities, the process model, is constructed as a directed, acyclic, weighted, colored graph. The nodes of the graph represent the activities which are performed. The edges of the graph, the control connectors, describe the potential sequence of execution of the activities. Definition of the process graph is via the IBM MQSeries Flow Definition Language (FDL) or the built-in graphical editor. The runtime

component of the workflow manager interprets the process graph and distributes the execution of activities to the right person at the right place, e. g. by assigning tasks to a work list according to the respective person, wherein said work list is stored as digital data within said workflow or process management computer system.

During operation of the system, the WFMS accesses a database, where the process models and their instantiations, the process instances, are stored. The size of the WFMS database can become very large. The database of the WFMS of a typical e-commerce company for example can easily reach the size of 100 GB.

The disadvantage of such a large database is that the performance associated with accessing of the database is getting worse the larger the database becomes.

#### Object of the Invention

The invention is based on the object to optimize the performance of a WFMS.

#### Summary and Advantages of the Invention

The objectives of the invention are solved by the independent claims. Further advantageous arrangements and embodiments of the invention are set forth in the respective subclaims.

The invention relates to a method of optimizing a Workflow-Management-System (WFMS), said method being executable by said WFMS on at least one computer system, said WFMS accesses a database comprising of at least one process model and instantiations of said process model (process instances). The method suggests to transfer objects of the database to an archive database (archive function). This transfer is preferably carried out in case that a predetermined event occurs or if



these objects are not currently used by the WFMS. Preferably the objects to be transfered to the archive database are process instances. These process instances are preferably selected among all instances of a certain process model depending on the value of certain properties of this process model. The objects of the database which are transfered to the archive database can also be process models. Additionally the data that is managed by the applications that implement the various activities of the process model can be transfered too by having user programs moving the data from the regular application store to an application archive store. Furthermore the method suggests to transfer the WFMS objects back to the WFMS database as well as to transfer the data in the application archive store back to the application store when the archived WFMS objects are needed again (restore function).

With the present invention the size of the WFMS database as well as the size of the application stores managed by the activity implementations can be minimized. The most important advantage of the current invention is that the smaller the size of the repository, the better is the performance associated with accessing the database.

By implementing the present invention the performance of the WFMS is improved.

#### Brief Description of the Drawings

Fig.1                    shows a definition of a WFMS system with enabled archive processing according to an embodiment of the present invention,

Fig. 2                   shows a definition of a process model with enabled archive processing according to an embodiment of the present invention,

- Fig. 3 shows commands to archive and to restore process instances according to an embodiment of the present invention,
- Fig. 4 shows a definition of automatic archiving of a process model according to an embodiment of the present invention,
- Fig. 5 shows commands to archive and to restore on model level according to an embodiment of the present invention,
- Fig. 6 shows a definition of a program for archiving/restoring of associated data and a definition of a process model with archiving/restoring of associated data according to an embodiment of the present invention,
- Fig. 7 shows a definition of a process with detailed archiving/restoring of associated data according to a further embodiment of the present invention.

#### Description of the Preferred Embodiment

The current invention is illustrated based on IBM's MQSeries Workflow workflow management system. Of course any other WFMS could be used instead. Furthermore the current teaching applies also to any other type of system which offers WFMS functionalities not as a separate WFMS but within some other type of system.

#### Introduction

The following is a short outline on the basic concepts of a workflow management system based on IBM's MQSeries Workflow WFMS as far as it is of importance for the current invention:

From an enterprise point of view the management of business processes is becoming increasingly important: business processes or process for short control which piece of work will be performed by whom and which resources are exploited for this work, i.e. a business process describes how an enterprise will achieve its business goals. A WFMS may support both, the modeling of business processes and their execution.

Modeling of a business process as a syntactical unit in a way that is directly supported by a software system is extremely desirable. Moreover, the software system can also work as an interpreter basically getting as input such a model: The model, called a process model or workflow model, can then be instantiated and the individual sequence of work steps depending on the context of the instantiation of the model can be determined. Such a model of a business process can be perceived as a template for a class of similar processes performed within an enterprise; it is a schema describing all possible execution variants of a particular kind of business process. An instance of such a model and its interpretation represents an individual process, i.e. a concrete, context dependent execution of a variant prescribed by the model. A WFMS facilitates the management of business processes. It provides a means to describe models of business processes (build time) and it drives business processes based on an associated model (run time). The meta model of IBM's WFMS MQSeries Workflow, i.e. the syntactical elements provided for describing business process models, and the meaning and interpretation of these syntactical elements, is described next.

A process model is a complete representation of a process, comprising a process diagram and the settings that define the logic behind the components of the diagram. Important components of a MQSeries Workflow process model are:

- Processes
- Activities

- Blocks
- Control Flows
- Connectors
- Data Containers
- Data Structures
- Programs
- Staff

Not all of these elements will be described below.

Activities are the fundamental elements of the meta model. An activity represents a business action that is from a certain perspective a semantic entity of its own.

A MQSeries Workflow process model consists of the following types of activities:

Program activity: Has a program assigned to perform it. The program is invoked when the activity is started. In a fully automated workflow, the program performs the activity without human intervention. Otherwise, the user must start the activity by selecting it from a runtime work list.

Process activity: Has a (sub-)process assigned to perform it. The process is invoked when the activity is started. A process activity represents a way to reuse a set of activities that are common to different processes.

The flow of control, i.e. the control flow through a running process determines the sequence in which activities are executed. The MQSeries Workflow workflow manager navigates a path through the process.

The results that are in general produced by the work represented by an activity is put into an output container, which is associated with each activity. Since an activity will in general

require to access output containers of other activities, each activity is associated in addition with an input container too.

Connectors link activities in a process model. Using connectors, one defines the sequence of activities and the transmission of data between activities. Since activities might not be executed arbitrarily they are bound together via control connectors. A control connector might be perceived as a directed edge between two activities; the activity at the connector's end point cannot start before the activity at the start point of the connector has finished (successfully). Control connectors model thus the potential flow of control within a business process model. Data connectors specify the flow of data in a workflow model. A data connector originates from an activity or a block, and has an activity or a block as its target. One can specify that output data is to go to one target or to multiple targets. A target can have more than one incoming data connector.

Process definition includes modeling of activities, control connectors between the activities, input/output container, and data connectors. A process is represented as a directed acyclic graph with the activities as nodes and the control/data connectors as the edges of the graph. The graph is manipulated via a built-in graphic editor. The data containers are specified as named data structures. These data structures themselves are specified via the DataStructureDefinition facility. Program activities are implemented through programs. The programs are registered via the Program Definition facility. Blocks contain the same constructs as processes, such as activities, control connectors etc. Process activities are implemented as processes. These subprocesses are defined separately as regular, named processes with all its usual properties. Process activities offer great flexibility for process definition. It not only allows to construct a process through permanent refinement of activities into program and process activities (top-down), but also to build a process out of a set of existing processes

(bottom-up).

All programs which implement program activities are defined via the Program Registration Facility. Registered for each program is the name of the program, its location, and the invocation string. The invocation string consists of the program name and the command string passed to the program.

### Preparing archiving

The present invention uses an archive database in order to store data to be archived. The archive database has the same structure as the normal database. The archive database is preferably located on a different device than the normal database. This provides for better performance when accessing both databases. It is typically allocated by the WFMS automatically when archiving for the WFMS is enabled. Other options are deferring the allocation until archiving is actually carried out.

In a preferred embodiment of the invention the enabling of the archive/restore function of the WFMS is performed using a definition as shown in Fig. 1. For this purpose a new keyword ARCHIVE\_SUPPORT 100 is added to the specification of the WFMS system. This keyword 100 is used to specify whether archiving for the WFMS System1 is enabled (ARCHIVE\_SUPPORT YES) or not (ARCHIVE\_SUPPORT NO). It should be noted that as an example in all figures of this description the Flow Definition Language (FDL) of MQSeries Workflow is used.

Archiving and restoring of business processes requires additional processing on the side of the WFMS. This additional processing is, for example, to keep information in the WFMS's database that otherwise would be discarded, or to check whether an archived version exists for a business process. For this reason it must be ensured that archiving and restoring are valid operations for a particular process instance. Fig. 2 shows how

the archiving for a process model, e.g. a loan process carried out in a bank, is enabled. Thereby preferably the same keyword 100 as illustrated in Fig.1 is used.

#### Archiving of process instances

When a process model is defined as archiveable, a particular process instance can be archived and restored. To archive and restore a process instance new commands are added to the specification of the process model. Fig. 3 shows some of the typical commands of a preferred embodiment. Thereby the command ARCHIVE 300 archives a process instance with a given process instance identifier 301, whereas the command RESTORE 302 restores a process instance.

Archiving means the move of all information about a particular process instance from the WFMS database into the archive database. This moved information may also include the information about the process model that is used to carry out the particular process instance. Restoring means the move of all information about a particular instance from the archive database to the WFMS database. This moved information may also includes the information about the process model that is used to carry out the particular process instance.

Archiving/Restoring is preferably carried out by a special designed archive/restore component which is part of the WFMS. Alternatively the archive/restore component can be implemented as an external component (e.g. a 'plug-in' component).

Quite often parts of a process model are carried out automatically, that means without user intervention. Then performing archiving and restoring via commands can only be an option to be used sparingly, since this approach requires interactions from the end user or administrator, performed e.g. via an appropriate programming interface.

Alternatively archiving can be defined as a time-controlled activity for a particular process model. Figure 4 shows the according definition for this approach. For this purpose the new keyword ARCHIVE 400 is added to the specification of the WFMS system. The ARCHIVE keyword 400 allows to specify when automatic archiving should occur. In the described example it defines that a particular process instance of the process model 'Loan Process' is archived when the process instance is idle for more than four days. The specification for the ARCHIVE keyword is not limited to being able to specify a particular time, but could be any arbitrary complex Boolean expression. In this case, archiving is performed if the Boolean expression evaluates to true.

Whereas archiving can be performed automatically according to the above embodiment, the restoring part would normally not be performed automatically. In most cases it will be sufficient to perform the restoring via an explicit call, e.g. the command of a user or the occurrence of a defined event. For example the restoring is performed if the WFMS requests to use the archived material, i.e. this material is transferred back to the WFMS database if it is needed again.

#### Context based archiving

Whereas in Fig.3 the archiving/restoring has been described with regard to the process instance level, the method of archiving/restoring can be applied to a collection of process instances i.e. to the process model level as well.

In this embodiment all process instances of a particular process model having certain properties are archived, e.g. all process-instances with a loan larger than \$10.000. For this purpose the appropriate instances of a process model have to be selected.



Figure 5 shows a preferred embodiment of according archive and restore commands. Thereby <Process Model Name> 500 identifies the process model. The selection is performed using the <Properties Operator Value> 501, which specifies the values that process instances of the specified process model must meet.

Properties can be any property that the user defines for the process model as well as properties automatically managed by the WFMS. User-defined properties are defined as fields in the input or output container of the process model or the input and output container of an activity. Assuming that the process input container of the process model LOAN\_PROCESS contains a field LOAN\_AMOUNT, which contains the associated loan amount, then the specification (ProcessInputContainer.LOAN\_AMOUNT > 50000) would select all process instances of the process model LOAN\_PROCESS where the loan amount is greater \$50.000. A typical system managed property is the date, the process instance was started. Thus a specification (START\_DATE < 4/10/99) would select all process instances that have been started before October 10th, 1999.

The <Properties Operator Value> 501 can comprise an arbitrary complex Boolean expression. Depending on the truth value of this Boolean predicate the WFMS performs the archiving/restoring of the process instances of the process model defined by <Process Model Name> 500.

In a further embodiment of the invention not only the process instances but the process models itself are archived/restored. This is especially applicable if all process instantiations of a particular process model are already archived.

#### Archiving of associated data

Archiving process instances as described above however may not

be sufficient. Workflow-based applications consist of a process model and the appropriate activity implementations. These activity implementations also manage data. For a complete archive, the data managed by the activity implementation is also be archived. If, for example, an activity implementation manages customer records, then the customer record managed for a particular process instance should also be archived. Thereby preferably those data is archived, which is managed by the programs that implemented the activities of the process model from which process instances are transfered to the archive database.

The data managed by the activity implementation is maintained in an application store, which can be any datastore. Because the WFMS normaly has no knowledge about the data managed by the activity implementation, e.g. their location, special designed means, e.g. programs, are utilized to move the data from the regular application store to an application archive store and vice versa. Preferably the application archive store is located on a different device than the application store.

Fig. 6 shows a preferred embodiment of the invention where data associated with a process is archived. Thereby the USING PROGRAM keyword 600 identifies the program 601, 602 that is called when a business process is archived or restored. Application programing interfaces provide the called programs 601, 602 with appropriate data, such as container contents, so that the programs can take the appropriate actions.

In the embodiment the archive/restore program pair 601, 602 is used to archive/restore all activities of the process model 'Loan Process'. That means, that these programs 601, 602 must know the complete structure of the process to be archived/restored. Therefore these programs are relatively complex.

An even further improved approach is described next. Fig. 7 shows such a preferred embodiment, where detailed archiving of associated data is performed. Thereby each program 701 (Pgm1, Pgm2, Pgm3) of an activity 700 (Activity1, Activity2, Activity3) is associated with an archive program 702 (Pgm1A, Pgm2A, Pgm3A) and a restore program 702 (Pgm1R, Pgm2R, Pgm3R).

During normal execution of the loan process the activities 1, 2 and 3, i.e. the programs Pgm1, Pgm2 and Pgm3 are executed. If the process is archived, then the WFMS reverses the executed graph and carries out this new graph by invoking the appropriate programs defined via the ARCHIVE keyword. If, for example, the process is archived after execution of Activity2, then the WFMS invokes the programs Pgm2A and Pgm1A during archiving. Similiarly, the programs Pgm1R and Pgm2R are invoked, when the business process is restored.

In a further embodiment of the invention the program versions of the programs Pgm1, Pgm2 and Pgm3 are archived additionally to the associated data. By archiving the program versions it is ensured that after restoring the process is carried out using the same program versions as used at the time prior to archiving.

The present invention can be realized in hardware, software, or a combination of hardware and software. A WFMS according to the present invention can be realized in a centralized fashion in one computer system, or in a distributed fashion where different elements are spread across several interconnected computer systems. Any kind of computer system - or other apparatus adapted for carrying out the methods described herein - is suited. A typical combination of hardware and software could be a general purpose computer system with a computer program that, when being loaded and executed, controls the computer system such that it carries out the methods described herein. The present invention can also be embedded in a computer program

product, which comprises all the features enabling the implementation of the methods described herein, and which - when loaded in a computer system - is able to carry out these methods.

Computer program means or computer program in the present context mean any expression, in any language, code or notation, of a set of instructions intended to cause a system having an information processing capability to perform a particular function either directly or after either or both of the following a) conversion to another language, code or notation; b) reproduction in a different material form.

## C L A I M S

1. A method of optimizing a Workflow-Management-System (WFMS), said method being executable by said WFMS on at least one computer system, said WFMS accesses a database comprising at least one process model and instantiations of said process model (process instances), said method is characterized in that it comprises the step of transferring objects of this database to an archive database.
2. The method of claim 1, characterized in that the step of transferring objects of the database to the archive database is carried out in case that a predetermined event occurs.
3. The method of claim 1, characterized in that the step of transferring objects of the database to the archive database is carried out if these objects are not currently used by the WFMS.
4. The method of claim 1, characterized in that the objects to be transfered to the archive database are process instances.
5. The method of claim 4, characterized in that the process instances to be transfered to the archive database are selected among the instances of a certain process model depending on the value of certain properties of this process model.
6. The method of claim 4 or 5, characterized in that the method comprises the further step of transferring from an application store to an application archive store data which is managed by the programs that implemented the activities of the process model from which process instances are transfered to the archive database.

7. The method of claim 1, characterized in that the objects to be transfered to the archive database are process models.
8. The method of claim 1, characterized in that the method comprises the further step of transferring these objects back to the database.
9. The method of claim 6, characterized in that the method comprises the further step of transferring these data from the application archive store back to the application store.
10. The method of claim 8 or 9, characterized in that these objects are transfered back to the database when they are needed again.
11. A system comprising means adapted for carrying out the steps of the method according to anyone of the preceding claims 1 to 10, whereas the system comprises an archiving database.
12. A data processing program comprising software code portions for performing the method according to anyone of the preceding claims 1 to 10 when the program is executed in a data processing system.
13. A computer program product comprising computer readable program means for causing a computer to perform the method according to anyone of the preceding claims 1 to 10 when the program is executed in a computer.

## A B S T R A C T

EPO - Munich  
38  
03. Juni 2000

The invention relates to a method of optimizing a Workflow-Management-System (WFMS), said method being executable by said WFMS on at least one computer system, said WFMS accesses a database comprising of at least one process model and instantiations of said process model (process instances). The method suggests to transfer objects of the database to an archive database (archive function). This transfer is preferably carried out in case that a predetermined event occurs or if these objects are not currently used by the WFMS. Preferably the objects to be transfered to the archive database are process instances. These process instances are preferably selected among all instances of a certain process model depending on the value of certain properties of this process model. The objects of the database which are transfered to the archive database can also be process models. Additionally the data that is managed by the applications that implement the various activities of the process model can be transfered too by having user programs moving the data from the regular application store to an application archive store. Furthermore the method suggests to transfer the WFMS objects back to the WFMS database as well as to transfer the data in the application archive store back to the application store when the archived WFMS objects are needed again (restore function).

(Fig. 1)

**THIS PAGE BLANK (USPTO)**



(Drawings)

EPO - Munich  
38  
03. Juni 2000

100  
SYSTEM System1  
ARCHIVE\_SUPPORT YES  
END System1

FIG.1

PROCESS LoanProcess  
ARCHIVE\_SUPPORT YES  
END

FIG.2

300 ARCHIVE <Process Instance Id>  
RESTORE <Process Instance Id> 301

FIG.3

302  
400 PROCESS LoanProcess  
ARCHIVE\_SUPPORT YES  
ARCHIVE AFTER 4 DAYS IDLE  
END

FIG.4

501 ARCHIVE <Process Model Name>  
<Properties Operator Value> 500  
RESTORE <Process Model Name>  
<Properties Operator Value>

FIG.5

```
PROGRAM LoanDataArchive
END LoanDataArchive
601
PROGRAM LoanDataRestore
END LoanDataRestore
602
PROCESS LoanProcess
  ARCHIVE_SUPPORT YES
  ARCHIVE AFTER 4 DAYS IDLE
  USING PROGRAM LoanDataArchive
  RESTORE USING PROGRAM LoanDataRestore
600
END
```

FIG.6

```
PROCESS LoanProcess
  ARCHIVE_SUPPORT YES
  ARCHIVE AFTER 4 DAYS IDLE
  PROGRAM_ACTIVITY Activity1
    PROGRAM Pgm1
      ARCHIVE Pgm1A
      RESTORE Pgm1R
    700
  701
END Activity1
  PROGRAM_ACTIVITY Activity2
    PROGRAM Pgm2
      ARCHIVE Pgm2A
      RESTORE Pgm2R
    702
  703
END Activity2
  PROGRAM_ACTIVITY Activity3
  PROGRAM Pgm3
  ARCHIVE Pgm3A
  RESTORE Pgm3R
END Activity3
END
```

FIG.7